



# tesa® Roller permanent

## Product Information



BNR 59100, 59110, 59151, 59156, 59606

### Product Description

The tesa® Roller Permanent Gluing ecoLogo® is the convenient way to apply a precisely defined strip of glue for reliable and durable adhesion.

### Product Features

- Strong adhesion
- Improved functionality due to optimised tip
- Clean, fast and permanent bonding
- Glues paper, cardboard, photos
- Reddish glue shows where adhesive has been applied
- Tear-resistant backing (PET)
- Solvent-free
- 100% recycled plastic (housing), refill 61% recycled plastic (without tape)
- Packaging: 80% recycled cardboard, blister without PVC

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |            |       |                    |         |
|------------|-------|--------------------|---------|
| • Recycled | 100 % | • Type of adhesive | acrylic |
|------------|-------|--------------------|---------|

### Properties/Performance Values

- |                        |                              |   |  |
|------------------------|------------------------------|---|--|
| • Humidity resistance  | no                           | • Solvent free                              | yes                                      |
| • Material             | Recycled PS<br>(polystyrene) | • Suitable for right and/or left<br>handers | For right and left<br>hander             |
| • Residue free removal | no                           | • Suitable surfaces                         | Paper, Cardboard,<br>Most plastic, Glass |
| • Reusable             | yes                          |   |  |



# tesa<sup>®</sup> Roller permanent

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59100>